



Figure similar

SIPLUS NET CP 343-1 Advanced based on 6GK7343-1GX31-0XE0 with conformal coating, 0...+60 °C, for connection of the SIMATIC S7-300 CPU to Ind. Ethernet; PROFINET IO controller and/or IO Device; RT and RT and IRT IRT, MRP, PROFINET CBA; TCP/IP ISO, UDP, S7 communication, S5-compatible communication, (send/receive) with fetch/write with and without RFC 1006, multicast diagnostics extension,SNMP,DHCP, FTP client/server, email, Gigabit-SS1X RJ45 (10/100/1000); PROFINET interface 2x RJ45(10/100 Mbit) PROFINET CBA; security

### transfer rate

transfer rate

- at the 1st interface 10 ... 1000 Mbit/s
- at the 2nd interface 10 ... 100 Mbit/s

### interfaces

number of interfaces / according to Industrial Ethernet

3

number of electrical connections

- at the 1st interface / according to Industrial Ethernet 1
- at the 2nd interface / according to Industrial Ethernet 2
- for power supply 1

type of electrical connection

- at the 1st interface / according to Industrial Ethernet RJ45 port
- at the 2nd interface / according to Industrial Ethernet RJ45 port

type of electrical connection

- for power supply 2-pole plugable terminal block

design of the removable storage

- C-PLUG Yes

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / 1 / from backplane bus

5 V

supply voltage / external

24 V

supply voltage / external / at DC / rated value

24 V

relative positive tolerance / at DC / at 24 V

20 %

relative negative tolerance / at DC / at 24 V

15 %

consumed current

- from backplane bus / at DC / at 5 V / typical 0.14 A
- from external supply voltage / at DC / at 24 V / typical 0.48 A
- from external supply voltage / at DC / at 24 V / maximum 0.62 A

power loss [W]

14.7 W

### ambient conditions

ambient temperature

- for vertical installation / during operation 0 ... 40 °C
- for horizontally arranged busbars / during operation 0 ... 60 °C
- during storage -40 ... +70 °C
- during transport -40 ... +70 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity

<ul style="list-style-type: none"> <li>with condensation / according to IEC 60068-2-38 / maximum</li> </ul>	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> </ul>	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> </ul>	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-6</li> </ul>	Yes
resistance to mechanically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> </ul>	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
<b>design, dimensions and weights</b>	
module format	Compact module
width	80 mm
height	125 mm
depth	120 mm
net weight	0.8 kg
fastening method <ul style="list-style-type: none"> <li>S7-300 rail mounting</li> </ul>	Yes
<b>performance data / open communication</b>	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
data volume <ul style="list-style-type: none"> <li>as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	8 Kibyte
<ul style="list-style-type: none"> <li>as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum</li> </ul>	2 Kibyte
number of Multicast stations	16
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication <ul style="list-style-type: none"> <li>maximum</li> </ul>	16
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	48
<b>performance data / IT functions</b>	
number of possible connections <ul style="list-style-type: none"> <li>as client / by means of FTP / maximum</li> </ul>	10
<ul style="list-style-type: none"> <li>as server / by means of FTP / maximum</li> </ul>	2
number of possible connections <ul style="list-style-type: none"> <li>as server / by means of HTTP / maximum</li> </ul>	4
<ul style="list-style-type: none"> <li>as email client / maximum</li> </ul>	1
data volume / as user data for email / maximum	8 Kibyte
storage capacity / of the user memory	

<ul style="list-style-type: none"> <li>● as flash memory file system</li> </ul>	28 MiByte
<ul style="list-style-type: none"> <li>● as RAM</li> </ul>	30 MiByte
number of possible write cycles / of the flash memory cells	100000
<b>performance data / PROFINET communication / as PN IO controller</b>	
product function / PROFINET IO controller	Yes
number of PN IO devices / on PROFINET IO controller / operable / total	128
number of PN IO IRT devices / on PROFINET IO controller / operable	128
number of external PN IO lines / with PROFINET / per rack	1
data volume	
<ul style="list-style-type: none"> <li>● as user data for input variables / as PROFINET IO controller / maximum</li> </ul>	4 KiByte
<ul style="list-style-type: none"> <li>● as user data for output variables / as PROFINET IO controller / maximum</li> </ul>	4 KiByte
<ul style="list-style-type: none"> <li>● as user data for input variables per PN IO device / as PROFINET IO controller / maximum</li> </ul>	1433 byte
<ul style="list-style-type: none"> <li>● as user data for output variables per PN IO device / as PROFINET IO controller / maximum</li> </ul>	1433 byte
<ul style="list-style-type: none"> <li>● as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>● as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum</li> </ul>	240 byte
<b>performance data / PROFINET communication / as PN IO device</b>	
product function / PROFINET IO device	Yes
data volume	
<ul style="list-style-type: none"> <li>● as user data for input variables / as PROFINET IO device / maximum</li> </ul>	1024 byte
<ul style="list-style-type: none"> <li>● as user data for output variables / as PROFINET IO device / maximum</li> </ul>	1024 byte
<ul style="list-style-type: none"> <li>● as user data for input variables / for each sub-module as PROFINET IO device</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>● as user data for output variables / for each sub-module as PROFINET IO device</li> </ul>	240 byte
<ul style="list-style-type: none"> <li>● as user data for the consistency area for each sub-module</li> </ul>	240 byte
number of submodules / per PROFINET IO-Device	32
<b>performance data / PROFINET CBA</b>	
number of remote connection partners / with PROFINET CBA	64
number of connections / with PROFINET CBA / total	1000
data volume	
<ul style="list-style-type: none"> <li>● as user data for digital inputs / with PROFINET CBA / maximum</li> </ul>	8 KiByte
<ul style="list-style-type: none"> <li>● as user data for digital outputs / with PROFINET CBA / maximum</li> </ul>	8 KiByte
<ul style="list-style-type: none"> <li>● as user data for arrays and data types / in the case of acyclic transmission / with PROFINET CBA / maximum</li> </ul>	8 KiByte
<ul style="list-style-type: none"> <li>● as user data for arrays and data types / with PROFINET CBA / with cyclical transfer / maximum</li> </ul>	250 byte
<ul style="list-style-type: none"> <li>● as user data for arrays and data types / with PROFINET CBA / in the case of local interconnection / maximum</li> </ul>	2400 byte
<b>performance data / PROFINET CBA / remote interconnection / with acyclic transfer</b>	
update time / of the remote interconnections / in the case of acyclic transmission / with PROFINET CBA	100 ms
number of remote connections to input variables / in the case of acyclic transmission / with PROFINET CBA / maximum	128
number of remote connections to output variables / in the case of acyclic transmission / with PROFINET CBA / maximum	128
data volume	
<ul style="list-style-type: none"> <li>● as user data for remote interconnections with input variables / in the case of acyclic transmission / with PROFINET CBA</li> </ul>	8 KiByte
<ul style="list-style-type: none"> <li>● as user data for remote interconnections with output variables / in the case of acyclic transmission / with PROFINET CBA</li> </ul>	8 KiByte
<b>performance data / PROFINET CBA / remote interconnection / with cyclic transfer</b>	
update time / of the remote interconnections / with cyclical transfer / with PROFINET CBA	8 ms

number of remote connections to input variables / with PROFINET CBA / with cyclic transfer / maximum	200
number of remote connections to output variables / with cyclical transfer / with PROFINET CBA / maximum	200
data volume	
<ul style="list-style-type: none"> <li>as user data for remote interconnections with input variables / with cyclical transfer / with PROFINET CBA / maximum</li> </ul>	2000 byte
<ul style="list-style-type: none"> <li>as user data for remote interconnections with output variables / with cyclical transfer / with PROFINET CBA / maximum</li> </ul>	2000 byte
<b>performance data / PROFINET CBA / HMI variables via PROFINET / acyclic</b>	
number of connectable HMI stations / for HMI variables / in the case of acyclic transmission / with PROFINET CBA	3
update time / of the HMI variables / in the case of acyclic transmission / with PROFINET CBA	500 ms
number of HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	200
data volume / as user data for HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	8 Kibyte
<b>performance data / PROFINET CBA / device-internal interconnections</b>	
number of internal connections / with PROFINET CBA / maximum	256
data volume / of the internal connections / with PROFINET CBA / maximum	2400 byte
<b>performance data / PROFINET CBA / interconnections to constants</b>	
number of connections with constants / with PROFINET CBA / maximum	200
data volume / as user data for interconnections with constants / with PROFINET CBA / maximum	4096 byte
<b>performance data / PROFINET CBA / PROFIBUS proxy functionality</b>	
product function / with PROFINET CBA / PROFIBUS proxy functionality	No
<b>performance data / telecontrol</b>	
protocol / is supported	
<ul style="list-style-type: none"> <li>TCP/IP</li> </ul>	Yes
<b>product functions / management, configuration, engineering</b>	
product function / MIB support	Yes
protocol / is supported	
<ul style="list-style-type: none"> <li>SNMP v1</li> <li>SNMP v3</li> <li>DCP</li> <li>LLDP</li> </ul>	Yes Yes Yes Yes
configuration software	
<ul style="list-style-type: none"> <li>required</li> <li>for PROFINET CBA / required</li> </ul>	STEP7 V5.5 SP2 HF1 or higher / STEP 7 Professional V12 (TIA Portal) or higher SIMATIC iMap V3.0 SP4 and higher
identification & maintenance function	
<ul style="list-style-type: none"> <li>I&amp;M0 - device-specific information</li> <li>I&amp;M1 - higher level designation/location designation</li> </ul>	Yes Yes
<b>product functions / diagnostics</b>	
product function / web-based diagnostics	Yes
<b>product functions / switch</b>	
product feature / switch	Yes
product function	
<ul style="list-style-type: none"> <li>switch-managed</li> <li>with IRT / PROFINET IO switch</li> <li>configuration with STEP 7</li> </ul>	No Yes Yes
<b>product functions / redundancy</b>	
product function	
<ul style="list-style-type: none"> <li>ring redundancy</li> <li>redundancy manager</li> </ul>	Yes Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
<b>product functions / security</b>	
firewall version	stateful inspection

product function / with VPN connection	IPSec
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1
number of possible connections / with VPN connection	32
product function	
• password protection for Web applications	Yes
• ACL - IP-based	Yes
• ACL - IP-based for PLC/routing	Yes
• switch-off of non-required services	Yes
• blocking of communication via physical ports	Yes
• log file for unauthorized access	No

#### product functions / time

product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
• NTP	Yes

#### standards, specifications, approvals

reference code	
• according to IEC 81346-2:2019	KEC

#### further information / internet links

internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://siemens.com/cax">https://siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

#### security information

security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>
----------------------	---

#### Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

[Miscellaneous](#)

[Manufacturer Declaration](#)



EG-Konf.



[KC](#)



RCM

#### For use in hazardous locations

[CCC-Ex](#)



ATEX



IECEX

last modified:

2/28/2025



# ماكان كنترول