



Front connector (Digital 4X8E/A) S7-300

Front connector module with flat ribbon Cable connection for digital 32 I/O modules of the S7-300, Power supply over Spring terminals

| | |
|--|--|
| target system | SIMATIC S7-300 |
| suitability for use | Digital I/O modules |
| product type designation | Fully modular connection |
| product designation | Front connector module |
| Operating data / header | |
| operating voltage / at DC | |
| • rated value | 24 V |
| • lue | 60 V |
| • maximum | 60 V |
| current / rated value | 1 A |
| continuous current / at DC / per plug-in contact / maximum | 1 A |
| total current / maximum | 4 A |
| operating temperature | 0 ... 60 °C |
| ambient temperature | |
| • during operation | 0 ... 60 °C |
| • during storage | -40 ... +70 °C |
| number of poles | 40; of the front connector |
| manufacturer's article number / of device connector / usable | replacement for S7-300 40 pole |
| number of the plug contacts / of the electrical connection | 4 |
| type of electrical connection / for connecting cable | Plug-in connection |
| number of poles / at the 1st interface | 16; the IDC connector for the connection cable |
| position / of the terminal | at the top |
| type of electrical connection / for power supply | Spring clamp |
| number of terminals | 8; 4 x 1 x L+, 4 x 1 x M |
| width of screwdriver blade | 3.5 mm |
| product component / required / end cover plate | No |
| number of cables / per connection | 2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule. |
| stripped length | 6 mm |
| type of connectable conductor cross-sections / solid | No |
| connectable conductor cross-section | |
| • for flexible conductor / with core end processing | 0.25 ... 0.75 mm ² ; End sleeve according to DIN 46228 without plastic collar |
| • stranded | 0.25 ... 0.75 mm ² |
| • finely stranded / without core end processing | 0.25 ... 0.75 mm ² |
| • finely stranded / with core end processing | 0.25 ... 0.75 mm ² |
| type of wire end sleeve | |
| • without plastic sleeve / according to DIN 46228-1 | Length 5mm to 7mm |
| outer diameter / of the wire insulation | 2 mm; to the connection of the supply terminal |
| wire length / maximum | 30 m; between front connector module and terminal module |
| General data / header | |

| | |
|--|-----------------|
| mounting type | direct mounting |
| degree of pollution | 2 |
| overvoltage category | 2 |
| design tested acc. to type of protection / EEx e | No |
| certificate of suitability / cULus approval | Yes |
| reference code / according to IEC 81346-2 | XG |
| material / of the insulating body | other |
| color / of the enclosure | black |
| product feature / transparent | No |
| net weight | 0.081 kg |

last modified:

4/9/2025 



ماكان كنترول