

product type designation

PROFIBUS OLM/G12-1300 V4.0

PROFIBUS OLM/G12-1300 V4.0 optical link module with 1 RS 485 and 2 glass fiber optic cable interfaces (4 BFOC sockets), 1300 Nm shaft length for large distances with signaling contact and test port.



transfer rate	
transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
transfer rate / with PROFIBUS PA	45.45 kbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	3
number of electrical connections	
• for network components or terminal equipment	1
• for measuring device	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
type of electrical connection	
• for network components or terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
number of optical interfaces / for fiber optic cable	2
design of the optical interface / for fiber optic cable	BFOC port
optical data	
attenuation factor / of the FOC transmission link	
• for glass FOC with 10/125 μm or 9/125 μm / at 0.5 dB/km / maximum	8 dB
propagation delay [bit]	6.5 bit
connectable optical power relative to 1 mW	
• for glass FOC with 10/125 μm or 9/125 μm / at 0.5 dB/km	-19 dB
optical sensitivity relating to 1 mW	
• for glass FOC with 10/125 μm or 9/125 μm / at 0.5 dB/km	-29 dB
wavelength / of the optical interface / note	1310 nm, single-mode
wire length	
• for glass FOC with 10/125 μm or 9/125 μm / at 0.5 dB/km / maximum	15 km
signal inputs/outputs	
operating voltage / of the signaling contacts / at DC / rated value	24 V
operational current / of the signaling contacts / at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / at DC / rated value	24 V
supply voltage / at DC	18.8 ... 28.8 V
product component / fusing at power supply input	Yes
consumed current / at DC / at 24 V / maximum	0.2 A

ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP40
design, dimensions and weights	
design	compact
width	39.5 mm
height	112 mm
depth	74.5 mm
net weight	340 g
fastening method	
<ul style="list-style-type: none"> 35 mm DIN-rail mounting wall mounting 	Yes Yes
product functions / redundancy	
product function / ring redundancy	Yes
standards, specifications, approvals	
standard	
<ul style="list-style-type: none"> for safety / from CSA and UL for emitted interference for interference immunity 	UL 60950-1, CSA C22.2 Nr. 60950-1 EN 61000-6-4 (Class A) EN 61000-6-2
certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> CE marking C-Tick 	Yes Yes
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) French marine classification society (BV) Det Norske Veritas (DNV) Germanische Lloyd (GL) Lloyds Register of Shipping (LRS) Nippon Kaiji Kyokai (NK) 	Yes Yes Yes Yes Yes Yes
reference code	
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	KGC
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	No
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
<ul style="list-style-type: none"> total during manufacturing during operation after end of life 	165.41 kg 15.09 kg 150.26 kg 0.06 kg
further information / internet links	
internet link	
<ul style="list-style-type: none"> to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to website: Industrial communication to web page: SiePortal to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://siemens.com/industrial-communication https://sieportal.siemens.com/ https://www.automation.siemens.com/bilddb https://www.siemens.com/cax https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic,

state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



General Product Approval

EMV

For use in hazardous locations

Marine / Shipping

[Miscellaneous](#)



[KC](#)



Marine / Shipping

Environment



[NK / Nippon Kaiji Kyokai](#)



[Confirmation](#)

Environment



last modified:

2/18/2025

ماکان کنترول