

Siemens  
EcoTech



SIMATIC S7-1200 G2: failsafe compact CPU 1214FC DC/DC/DC; power supply: DC 20.4-28.8 V DC; onboard I/O: 14x DI 24 V DC; 10x DO 24 V DC; memory: program 300 KB data: 750 KB, retentivity: 20 KB



Figure similar

| General information  |  |
|--|--|
| Product type designation   | CPU 1214FC DC/DC/DC                      |
| Firmware version   | V1.0                                     |
| <ul style="list-style-type: none"> <li>FW update possible</li> </ul>       | Yes                                      |
| Product function   |  |
| <ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>             | Yes; I&M0 to I&M3                        |
| <ul style="list-style-type: none"> <li>SysLog</li> </ul>                   | Yes                                      |
| Engineering with   |  |
| <ul style="list-style-type: none"> <li>Programming package</li> </ul>      | STEP 7 V20 or higher                     |
| Supply voltage   |  |
| Rated value (DC)   |  |
| <ul style="list-style-type: none"> <li>24 V DC</li> </ul>                  | Yes                                      |
| permissible range, lower limit (DC)  | 20.4 V                                   |
| permissible range, upper limit (DC)  | 28.8 V                                   |
| Reverse polarity protection  | Yes                                      |
| Input current  |  |
| Current consumption (rated value)  | 145 mA; CPU only                         |
| Current consumption, max.  | 1 000 mA; CPU with all expansion modules |
| Inrush current, max.   | 12 A; at 28.8 V DC                       |
| $I^2t$   | 0.5 A <sup>2</sup> ·s                    |
| Output current   |  |
| for backplane bus (5 V DC), max.   | 1 600 mA; Max. 5 V DC for SM and CM      |
| Encoder supply   |  |
| 24 V encoder supply  |  |
| <ul style="list-style-type: none"> <li>24 V</li> </ul>                     | Yes; L+ minus 4 V DC min.                |
| <ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul> | Yes                                      |
| <ul style="list-style-type: none"> <li>Output current, max.</li> </ul>     | 400 mA                                   |
| Power loss   |  |
| Power loss, typ.   | 3.5 W                                    |
| Memory   |  |
| Work memory  |  |
| <ul style="list-style-type: none"> <li>integrated</li> </ul>               | 1 050 kbyte                              |
| <ul style="list-style-type: none"> <li>integrated (for program)</li> </ul> | 300 kbyte                                |
| <ul style="list-style-type: none"> <li>integrated (for data)</li> </ul>    | 750 kbyte                                |
| Load memory  |  |
| <ul style="list-style-type: none"> <li>integrated</li> </ul>               | 8 Mbyte                                  |

|   |   |
|---|---|
| • Plug-in (SIMATIC Memory Card), max.                     | 32 Gbyte; with SIMATIC memory card  |
| <b>Backup</b>   |   |
| • present   | Yes   |
| • maintenance-free  | Yes   |
| • without battery   | Yes   |
| <b>CPU processing times</b>                               |   |
| for bit operations, typ.                                  | 37 ns; / instruction  |
| for word operations, typ.                                 | 30 ns; / instruction  |
| for floating point arithmetic, typ.                       | 74 ns; / instruction  |
| <b>CPU-blocks</b>   |   |
| Number of elements (total)                                | 4 000; Blocks (OB, FB, FC, DB) and UDTs   |
| <b>OB</b>   |   |
| • Number of free cycle OBs                                | 100   |
| • Number of time alarm OBs                                | 20  |
| • Number of delay alarm OBs                               | 20  |
| • Number of cyclic interrupt OBs                          | 20; with minimum OB 3x cycle of 1 ms  |
| • Number of process alarm OBs                             | 50  |
| • Number of DPV1 alarm OBs                                | 3   |
| • Number of isochronous mode OBs                          | 1   |
| • Number of startup OBs                                   | 100   |
| • Number of asynchronous error OBs                        | 4   |
| • Number of synchronous error OBs                         | 2   |
| • Number of diagnostic alarm OBs                          | 1   |
| <b>Data areas and their retentivity</b>                   |   |
| Retentive data area (incl. timers, counters, flags), max. | 20 kbyte  |
| <b>Flag</b>   |   |
| • Size, max.  | 8 kbyte; Size of bit memory address area  |
| <b>Local data</b>   |   |
| • per priority class, max.                                | 64 kbyte; max. 16 KB per block  |
| <b>Address area</b>                                       |   |
| <b>Process image</b>                                      |   |
| • Inputs, adjustable                                      | 1 kbyte   |
| • Outputs, adjustable                                     | 1 kbyte   |
| <b>Hardware configuration</b>                             |   |
| Number of modules per system, max.                        | 10  |
| <b>Time of day</b>  |   |
| <b>Clock</b>  |   |
| • Hardware clock (real-time)                              | Yes   |
| • Backup time   | 480 h; Typical  |
| • Deviation per day, max.                                 | 2 s; at 25 °C   |
| <b>Digital inputs</b>                                     |   |
| Number of digital inputs                                  | 14; Integrated  |
| • of which inputs usable for technological functions      | 8; HSC (High Speed Counting)  |
| Source/sink input   | Yes   |
| <b>Number of simultaneously controllable inputs</b>       |   |
| all mounting positions                                    |   |
| — up to 40 °C, max.                                       | 14  |
| <b>Input voltage</b>                                      |   |
| • Rated value (DC)  | 24 V  |
| • for signal "0"  | 5 V DC or 0.5 mA  |
| • for signal "1"  | 15 V DC at 2.5 mA   |
| <b>Input delay (for rated value of input voltage)</b>     |   |
| for standard inputs                                       |   |
| — parameterizable   | 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms |
| — at "0" to "1", min.                                     | 0.1 µs  |
| — at "0" to "1", max.                                     | 20 ms   |
| for interrupt inputs                                      |   |
| — parameterizable   | Yes   |
| for technological functions                               |   |
| — parameterizable   | single phase: 6 HSCs @ 100 kHz & 2 standard @ 30 kHz, quadrature phase: 6   |

HSCs @ 80 kHz & 2 standard @ 20 kHz

|   |  |
|---|--|
| <b>Cable length</b>   |  |
| <ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>  | <p>500 m; 50 m for technological functions</p> <p>300 m; for technological functions: No</p>   |
| <b>Digital outputs</b>  |  |
| Number of digital outputs   | 10; 20 kHz or 100 kHz  |
| <ul style="list-style-type: none"> <li>of which high-speed outputs</li> </ul>   | 4; 100 kHz (Qa.0 - Qa.3)   |
| Limitation of inductive shutdown voltage to   | L+ (-40 V)   |
| <b>Switching capacity of the outputs</b>  |  |
| <ul style="list-style-type: none"> <li>with resistive load, max.</li> <li>on lamp load, max.</li> </ul>   | <p>0.5 A</p> <p>5 W</p>  |
| <b>Output voltage</b>   |  |
| <ul style="list-style-type: none"> <li>for signal "0", max.</li> <li>for signal "1", min.</li> </ul>  | <p>0.1 V; with 10 kOhm load</p> <p>20 V</p>  |
| <b>Output current</b>   |  |
| <ul style="list-style-type: none"> <li>for signal "1" rated value</li> <li>for signal "0" residual current, max.</li> </ul>   | <p>0.5 A</p> <p>10 µA</p>  |
| <b>Output delay with resistive load</b>   |  |
| <ul style="list-style-type: none"> <li>"0" to "1", max.</li> <li>"1" to "0", max.</li> </ul>  | <p>1 µs; of the pulse outputs (Qa.0 to Qa.3), max. 1.0 µs; of the standard outputs (Qa.4 to Qb.1), max. 50 µs;</p> <p>3 µs; of the pulse outputs (Qa.0 to Qa.3), max. 3.0 µs; of the standard outputs (Qa.4 to Qb.1), max. 200 µs;</p> |
| <b>Switching frequency</b>  |  |
| <ul style="list-style-type: none"> <li>of the pulse outputs, with resistive load, max.</li> </ul>   | 100 kHz; 100 kHz max. (Qa.0 - Qa.3), 20 kHz max. (Qa.4 to Qb.1)  |
| <b>Relay outputs</b>  |  |
| <ul style="list-style-type: none"> <li>Number of relay outputs</li> </ul>   | 0  |
| <b>Cable length</b>   |  |
| <ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>  | <p>500 m</p> <p>150 m</p>  |
| <b>Analog inputs</b>  |  |
| Number of analog inputs   | 0  |
| <b>Analog outputs</b>   |  |
| Number of analog outputs  | 0  |
| <b>Encoder</b>  |  |
| Connectable encoders  |  |
| <ul style="list-style-type: none"> <li>2-wire sensor</li> </ul>   | Yes  |
| <b>1. Interface</b>   |  |
| Interface type  | PROFINET   |
| Isolated  | Yes  |
| automatic detection of transmission rate  | Yes  |
| Autonegotiation   | Yes  |
| Autocrossing  | Yes  |
| <b>Interface types</b>  |  |
| <ul style="list-style-type: none"> <li>RJ 45 (Ethernet)</li> <li>Number of ports</li> <li>integrated switch</li> </ul>  | <p>Yes</p> <p>2</p> <p>Yes</p>   |
| <b>Protocols</b>  |  |
| <ul style="list-style-type: none"> <li>IP protocol</li> <li>PROFINET IO Controller</li> <li>PROFINET IO Device</li> <li>SIMATIC communication</li> <li>Open IE communication</li> <li>Web server</li> <li>Media redundancy</li> </ul> | <p>Yes; IPv4</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Optionally also encrypted</p> <p>Yes</p> <p>Yes</p>  |
| <b>PROFINET IO Controller</b>   |  |
| <ul style="list-style-type: none"> <li>Transmission rate, max.</li> </ul>   | 100 Mbit/s   |
| <b>Services</b>   |  |
| <ul style="list-style-type: none"> <li>PG/OP communication</li> <li>Isochronous mode</li> <li>IRT</li> <li>PROFINergy</li> </ul>  | <p>Yes; encryption with TLS V1.3 pre-selected</p> <p>Yes</p> <p>Yes</p> <p>Yes; per user program</p>   |

|   |   |
|---|---|
| — Prioritized startup   | Yes   |
| — Number of IO devices with prioritized startup, max.                         | 16  |
| — Number of connectable IO Devices, max.                                      | 31  |
| — Of which IO devices with IRT, max.  | 31  |
| — Number of connectable IO Devices for RT, max.                               | 31  |
| — of which in line, max.  | 31  |
| — Activation/deactivation of IO Devices                                       | Yes   |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8   |
| — Updating time   | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |

#### Update time for IRT

|                          |               |
|--------------------------|---------------|
| — for send cycle of 1 ms | 1 ms to 16 ms |
| — for send cycle of 2 ms | 2 ms to 32 ms |
| — for send cycle of 4 ms | 4 ms to 64 ms |

#### Update time for RT

|                          |                |
|--------------------------|----------------|
| — for send cycle of 1 ms | 1 ms to 512 ms |
| — for send cycle of 2 ms | 2 ms to 512 ms |
| — for send cycle of 4 ms | 4 ms to 512 ms |

#### PROFINET IO Device

##### Services

|   |  |
|---|--|
| — PG/OP communication                               | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode                                  | No   |
| — IRT   | Yes  |
| — PROFINergy  | Yes; per user program                      |
| — Shared device                                     | Yes  |
| — Number of IO Controllers with shared device, max. | 2  |

#### Protocols

|                                   |     |
|-----------------------------------|-----|
| Supports protocol for PROFINET IO | Yes |
| PROFIsafe                         | Yes |
| PROFIBUS                          | No  |
| OPC UA                            | No  |
| AS-Interface                      | No  |

#### Protocols (Ethernet)

|          |     |
|----------|-----|
| • TCP/IP | Yes |
| • DHCP   | Yes |
| • SNMP   | Yes |
| • DCP    | Yes |
| • LLDP   | Yes |

#### Number of connections

|   |   |
|---|---|
| • Number of connections, max.                     | 128; via integrated interfaces of the CPU and connected CPs / CMs |
| • Number of connections reserved for ES/HMI/web   | 10  |
| • Number of connections via integrated interfaces | 88  |

#### Redundancy mode

##### Media redundancy

|        |  |
|--------|--|
| — MRP  | Yes; as MRP redundancy manager and/or MRP client |
| — MRPD | Yes  |

#### SIMATIC communication

|                               |     |
|-------------------------------|-----|
| • S7 routing                  | No  |
| • S7 communication, as server | Yes |
| • S7 communication, as client | Yes |

#### Open IE communication

|   |  |
|---|--|
| • TCP/IP  | Yes                                    |
| — Data length, max.                               | 8 kbyte                                |
| — several passive connections per port, supported | Yes                                    |
| • ISO-on-TCP (RFC1006)                            | Yes                                    |
| — Data length, max.                               | 8 kbyte                                |
| • UDP   | Yes                                    |
| — Data length, max.                               | 2 kbyte; 1 472 bytes for UDP broadcast |
| • DHCP  | Yes                                    |
| • DNS   | Yes                                    |

|  |  |
|--|--|
| • SNMP   | Yes  |
| • DCP  | Yes  |
| • LLDP   | Yes  |
| • Encryption   | Yes; Optional  |
| <b>Web server</b>  |  |
| • supported  | Yes  |
| • HTTPS  | Yes  |
| • web API  | Yes  |
| — Number of sessions, max.   | 30   |
| • User-defined websites  | Yes  |
| <b>Further protocols</b>   |  |
| • MODBUS   | Yes  |
| <b>communication functions / header</b>  |  |
| <b>S7 communication</b>  |  |
| • supported  | Yes  |
| • as server  | Yes  |
| • as client  | Yes  |
| • User data per job, max.  | See online help (S7 communication, user data size)   |
| <b>Number of connections</b>   |  |
| • overall  | PG Connections: 4 reserved; HMI Connections: 4 reserved / 82 max; S7 Connections: 78 max; Open User Connections: 78 max; Web Connections: 2 reserved / 80 max; Total Connections: 10 reserved / 88 max |
| <b>S7 message functions</b>  |  |
| Number of login stations for message functions, max.                           | 32   |
| Program alarms   | Yes  |
| Number of configurable program messages, max.                                  | 5 000  |
| Number of loadable program messages in RUN, max.                               | 2 500  |
| Number of simultaneously active program alarms                                 |  |
| • Number of program alarms   | 600  |
| • Number of alarms for system diagnostics                                      | 100  |
| • Number of alarms for motion technology objects                               | 160  |
| <b>Test commissioning functions</b>  |  |
| <b>Status/control</b>  |  |
| • Status/control variable  | Yes  |
| • Variables  | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters   |
| <b>Forcing</b>   |  |
| • Forcing  | Yes  |
| <b>Diagnostic buffer</b>   |  |
| • present  | Yes  |
| <b>Traces</b>  |  |
| • Number of configurable Traces  | 4  |
| • Memory size per trace, max.  | 512 kbyte  |
| <b>Interrupts/diagnostics/status information</b>                               |  |
| <b>Diagnostics indication LED</b>  |  |
| • RUN/STOP LED   | Yes  |
| • ERROR LED  | Yes  |
| • MAINT LED  | Yes  |
| <b>Supported technology objects</b>  |  |
| <b>Motion Control</b>  |  |
| • Number of available Motion Control resources for technology objects          | 800  |
| • Required Motion Control resources  |  |
| — per speed-controlled axis  | 40   |
| — per positioning axis   | 80   |
| — per synchronous axis   | 160  |
| — per external encoder   | 80   |
| — per output cam   | 20   |
| — per cam track  | 160  |
| — per probe  | 40   |
| • Number of available Extended Motion Control resources for technology objects | 40   |
| • Required Extended Motion Control resources                                   |  |

|   |  |
|---|--|
| — per cam (1 000 points and 50 segments)  | 2; 1000 points and 1 segment   |
| — for each set of kinematics  | 30   |
| • kinematics functions  |  |
| — kinematics with up to 4 interpolating axes  | Yes  |
| — kinematics with 5 or more interpolating axes  | No   |
| — user-defined kinematics   | No   |
| — SIMATIC Safe Kinematics   | No   |
| • Positioning axis  |  |
| — Number of positioning axes at motion control cycle of 4 ms (typical value)                  | 10   |
| — Number of positioning axes at motion control cycle of 8 ms (typical value)                  | 10   |
| <b>Integrated Functions</b>   |  |
| Counter   | Yes  |
| • Number of counters  | 8  |
| • Counting frequency, max.  | 100 kHz; Ia.0 to Ia.5: 100 kHz (80 kHz in quadrature mode), Ia.6 to Ib.5: 30 kHz (20 kHz in quadrature mode)   |
| Frequency measurement   | Yes  |
| PID controller  | Yes  |
| Number of pulse outputs   | 8; individually assigned to CPU and Signal Board   |
| Limit frequency (pulse)   | 100 kHz  |
| <b>Potential separation</b>   |  |
| Potential separation digital inputs   |  |
| • Potential separation digital inputs   | Yes; field side to logic: 707 V DC (type test)   |
| • between the channels  | No   |
| • Number of potential groups  | 1  |
| Potential separation digital outputs  |  |
| • Potential separation digital outputs  | Yes  |
| • between the channels  | No   |
| • Number of potential groups  | 1  |
| <b>EMC</b>  |  |
| Interference immunity against discharge of static electricity                                 |  |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2         | Yes  |
| — Test voltage at air discharge   | 8 kV   |
| — Test voltage at contact discharge   | 6 kV   |
| Interference immunity to cable-borne interference   |  |
| • Interference immunity on supply lines acc. to IEC 61000-4-4                                 | Yes  |
| • Interference immunity on signal cables acc. to IEC 61000-4-4                                | Yes  |
| Interference immunity against voltage surge   |  |
| • Interference immunity on supply lines acc. to IEC 61000-4-5                                 | Yes  |
| Interference immunity against conducted variable disturbance induced by high-frequency fields |  |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6                | Yes  |
| Emission of radio interference acc. to EN 55 011  |  |
| • Limit class A, for use in industrial areas  | Yes; Group 1   |
| • Limit class B, for use in residential areas   | Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |
| <b>Degree and class of protection</b>   |  |
| IP degree of protection   | IP20   |
| <b>Standards, approvals, certificates</b>   |  |
| Siemens Eco Profile (SEP)   | Siemens EcoTech  |
| CE mark   | Yes  |
| UL approval   | Yes  |
| cULus   | Yes  |
| FM approval   | No   |
| RCM (formerly C-TICK)   | Yes  |
| KC approval   | No   |
| Marine approval   | No   |
| Ecological footprint  |  |

|   |   |
|---|---|
| • environmental product declaration   | Yes; type 2 acc. to ISO 14021   |
| <b>Global warming potential</b>   |   |
| — global warming potential, (total) [CO2 eq]  | 68 kg   |
| — global warming potential, (during production) [CO2 eq]                                  | 14.4 kg   |
| — global warming potential, (during operation) [CO2 eq]                                   | 54.2 kg   |
| — global warming potential, (after end of life cycle) [CO2 eq]                            | -0.723 kg   |
| <b>Highest safety class achievable in safety mode</b>                                     |   |
| • Performance level according to ISO 13849-1  | PLe   |
| • SIL acc. to IEC 61508   | SIL 3   |
| <b>Probability of failure (for service life of 20 years and repair time of 100 hours)</b> |   |
| — Low demand mode: PFDavg in accordance with SIL3   | < 2.00E-05  |
| — High demand/continuous mode: PFH in accordance with SIL3                                | < 1.00E-09 up to an operational altitude of 3 000 m or < 2.00E-09 at an operating altitude greater than 3 000 m up to 5 000 m |
| <b>product functions / security / header</b>  |   |
| signed firmware update  | Yes   |
| Secure Boot   | Yes   |
| safely removing data  | No  |
| <b>Ambient conditions</b>   |   |
| <b>Free fall</b>  |   |
| • Fall height, max.   | 0.3 m; five times, in product package   |
| <b>Ambient temperature during operation</b>   |   |
| • min.  | -20 °C; No condensation   |
| • max.  | 40 °C; at max. voltages and max. specifications   |
| • horizontal installation, min.   | -20 °C; No condensation   |
| • horizontal installation, max.   | 60 °C; at rated voltages, 50 % of max. specification and alternate IO active  |
| • vertical installation, min.   | -20 °C; No condensation   |
| • vertical installation, max.   | 50 °C; at rated voltages, 50 % of max. specification and alternate IO active  |
| <b>Ambient temperature during storage/transportation</b>                                  |   |
| • min.  | -40 °C  |
| • max.  | 70 °C   |
| <b>Air pressure acc. to IEC 60068-2-13</b>  |   |
| • Operation, min.   | 540 hPa   |
| • Operation, max.   | 1 140 hPa   |
| • Storage/transport, min.   | 540 hPa   |
| • Storage/transport, max.   | 1 140 hPa   |
| <b>Altitude during operation relating to sea level</b>                                    |   |
| • Installation altitude, min.   | -1 000 m  |
| • Installation altitude, max.   | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual  |
| <b>Relative humidity</b>  |   |
| • Operation, max.   | 95 %; no condensation   |
| <b>Vibrations</b>   |   |
| • Vibration resistance during operation acc. to IEC 60068-2-6                             | 3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz  |
| • Operation, tested according to IEC 60068-2-6  | Yes   |
| <b>Shock testing</b>  |   |
| • tested according to IEC 60068-2-27  | Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms                                     |
| <b>Pollutant concentrations</b>   |   |
| • SO2 at RH < 60% without condensation  | SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free   |
| <b>configuration / header</b>   |   |
| <b>configuration / programming / header</b>   |   |
| <b>Programming language</b>   |   |
| — LAD   | Yes; incl. failsafe   |
| — FBD   | Yes; incl. failsafe   |
| — SCL   | Yes   |
| <b>Know-how protection</b>  |   |
| • User program protection/password protection   | Yes   |
| <b>Access protection</b>  |   |
| • protection of confidential configuration data   | Yes   |

- Protection level: Write protection Yes
- Protection level: Read/write protection Yes
- Protection level: Write protection for Failsafe Yes
- Protection level: Complete protection Yes
- User administration Yes; device-wide
- Number of users 100
- Number of groups 100
- Number of roles 50

programming / cycle time monitoring / header

- adjustable Yes

Dimensions

|        |        |
|--------|--------|
| Width  | 80 mm  |
| Height | 125 mm |
| Depth  | 100 mm |

Weights

|                 |       |
|-----------------|-------|
| Weight, approx. | 352 g |
|-----------------|-------|

Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-22-07    |
| eClass | 12      | 27-24-22-07    |
| eClass | 9.1     | 27-24-22-07    |
| eClass | 9       | 27-24-22-07    |
| eClass | 8       | 27-24-22-07    |
| eClass | 7.1     | 27-24-22-07    |
| eClass | 6       | 27-24-22-07    |
| ETIM   | 9       | EC000236       |
| ETIM   | 8       | EC000236       |
| ETIM   | 7       | EC000236       |

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[KC](#)

[Miscellaneous](#)



EMV

For use in hazardous locations

Functional Safety

[KC](#)



[CCC-Ex](#)

[Type Examination Certificate](#)

Environment

Industrial Communication



[PROFINET](#)

last modified:

4/1/2025