

Siemens
EcoTech



SIMATIC S7-1200 G2: compact CPU 1214C AC/DC/RLY; power supply: AC 85-264 V AC at 47-63 Hz; onboard I/O: 14x DI 24 V DC; 10 DO relay 2 A; memory: program 250 KB data: 750 KB, retentivity: 20 KB



| General information | |
|--|--|
| Product type designation | CPU 1214C AC/DC/Relay |
| Firmware version | V1.0 |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> SysLog | Yes |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V20 or higher |
| Supply voltage | |
| Rated value (AC) | |
| <ul style="list-style-type: none"> 120 V AC | Yes |
| <ul style="list-style-type: none"> 230 V AC | Yes |
| permissible range, lower limit (AC) | 85 V |
| permissible range, upper limit (AC) | 264 V |
| Line frequency | |
| <ul style="list-style-type: none"> permissible range, lower limit | 47 Hz |
| <ul style="list-style-type: none"> permissible range, upper limit | 63 Hz |
| Input current | |
| Current consumption (rated value) | 80 mA at 120 V AC; 44 mA at 240 V AC |
| Current consumption, max. | 480 mA at 120 V AC; 275 mA at 240 V AC |
| Inrush current, max. | 20 A; at 264 V |
| I ² t | 0.8 A ² ·s |
| Output current | |
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |
| Encoder supply | |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | Yes; 20.4 to 28.8V |
| <ul style="list-style-type: none"> Short-circuit protection | Yes |
| <ul style="list-style-type: none"> Output current, max. | 400 mA |
| Power loss | |
| Power loss, typ. | 4 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated | 1 000 kbyte |
| <ul style="list-style-type: none"> integrated (for program) | 250 kbyte |
| <ul style="list-style-type: none"> integrated (for data) | 750 kbyte |

| | |
|--|---|
| Load memory | |
| <ul style="list-style-type: none"> integrated | 8 Mbyte |
| <ul style="list-style-type: none"> Plug-in (SIMATIC Memory Card), max. | 32 Gbyte; with SIMATIC memory card |
| Backup | |
| <ul style="list-style-type: none"> present | Yes |
| <ul style="list-style-type: none"> maintenance-free | Yes |
| <ul style="list-style-type: none"> without battery | Yes |
| CPU processing times | |
| for bit operations, typ. | 37 ns; / instruction |
| for word operations, typ. | 30 ns; / instruction |
| for floating point arithmetic, typ. | 74 ns; / instruction |
| CPU-blocks | |
| Number of elements (total) | 4 000; Blocks (OB, FB, FC, DB) and UDTs |
| OB | |
| <ul style="list-style-type: none"> Number of free cycle OBs | 100 |
| <ul style="list-style-type: none"> Number of time alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of delay alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of cyclic interrupt OBs | 20; with minimum OB 3x cycle of 1 ms |
| <ul style="list-style-type: none"> Number of process alarm OBs | 50 |
| <ul style="list-style-type: none"> Number of DPV1 alarm OBs | 3 |
| <ul style="list-style-type: none"> Number of isochronous mode OBs | 1 |
| <ul style="list-style-type: none"> Number of startup OBs | 100 |
| <ul style="list-style-type: none"> Number of asynchronous error OBs | 4 |
| <ul style="list-style-type: none"> Number of synchronous error OBs | 2 |
| <ul style="list-style-type: none"> Number of diagnostic alarm OBs | 1 |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 20 kbyte |
| Flag | |
| <ul style="list-style-type: none"> Size, max. | 8 kbyte; Size of bit memory address area |
| Local data | |
| <ul style="list-style-type: none"> per priority class, max. | 64 kbyte; max. 16 KB per block |
| Address area | |
| Process image | |
| <ul style="list-style-type: none"> Inputs, adjustable | 1 kbyte |
| <ul style="list-style-type: none"> Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 10 |
| Time of day | |
| Clock | |
| <ul style="list-style-type: none"> Hardware clock (real-time) | Yes |
| <ul style="list-style-type: none"> Backup time | 480 h; Typical |
| <ul style="list-style-type: none"> Deviation per day, max. | 2 s; at 25 °C |
| Digital inputs | |
| Number of digital inputs | 14; Integrated |
| <ul style="list-style-type: none"> of which inputs usable for technological functions | 8; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V |
| <ul style="list-style-type: none"> for signal "0" | 5 V DC or 0.5 mA |
| <ul style="list-style-type: none"> for signal "1" | 15 V DC at 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 µs; 0.05 / 0.1 / 0.2 / 0.4 / 0.8 / 1.6 / 3.2 / 6.4 / 10.0 / 12.8 / 20.0 ms |
| — at "0" to "1", min. | 0.1 µs |
| — at "0" to "1", max. | 20 ms |
| for interrupt inputs | |
| — parameterizable | Yes |

| | |
|---|---|
| for technological functions | |
| — parameterizable | single phase: 6 HSCs @ 100 kHz & 2 standard @ 30 kHz, quadrature phase: 6 HSCs @ 80 kHz & 2 standard @ 20 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 300 m; for technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10; Relays |
| Switching capacity of the outputs | |
| • with resistive load, max. | 2 A |
| • on lamp load, max. | 30 W with DC, 200 W with AC |
| Output delay with resistive load | |
| • "0" to "1", max. | 10 ms; max. |
| • "1" to "0", max. | 10 ms; max. |
| Switching frequency | |
| • of the pulse outputs, with resistive load, max. | Not recommended |
| Relay outputs | |
| • Number of relay outputs | 10 |
| • Number of operating cycles, max. | mechanically 10 million, at rated load voltage 100 000 |
| Cable length | |
| • shielded, max. | 500 m |
| • unshielded, max. | 150 m |
| Analog inputs | |
| Number of analog inputs | 0 |
| Analog outputs | |
| Number of analog outputs | 0 |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| 1. Interface | |
| Interface type | PROFINET |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| • RJ 45 (Ethernet) | Yes |
| • Number of ports | 2 |
| • integrated switch | Yes |
| Protocols | |
| • IP protocol | Yes; IPv4 |
| • PROFINET IO Controller | Yes |
| • PROFINET IO Device | Yes |
| • SIMATIC communication | Yes |
| • Open IE communication | Yes; Optionally also encrypted |
| • Web server | Yes |
| • Media redundancy | Yes |
| PROFINET IO Controller | |
| • Transmission rate, max. | 100 Mbit/s |
| Services | |
| — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode | Yes |
| — IRT | Yes |
| — PROFlenergy | Yes; per user program |
| — Prioritized startup | Yes |
| — Number of IO devices with prioritized startup, max. | 16 |
| — Number of connectable IO Devices, max. | 31 |
| — Of which IO devices with IRT, max. | 31 |
| — Number of connectable IO Devices for RT, max. | 31 |
| — of which in line, max. | 31 |
| — Activation/deactivation of IO Devices | Yes |

| | |
|---|---|
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| — Updating time | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |
| Update time for IRT | |
| — for send cycle of 1 ms | 1 ms to 16 ms |
| — for send cycle of 2 ms | 2 ms to 32 ms |
| — for send cycle of 4 ms | 4 ms to 64 ms |
| Update time for RT | |
| — for send cycle of 1 ms | 1 ms to 512 ms |
| — for send cycle of 2 ms | 2 ms to 512 ms |
| — for send cycle of 4 ms | 4 ms to 512 ms |
| PROFINET IO Device | |
| Services | |
| — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode | No |
| — IRT | Yes |
| — PROFINergy | Yes; per user program |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 2 |
| Protocols | |
| Supports protocol for PROFINET IO | Yes |
| PROFIsafe | No |
| PROFIBUS | No |
| OPC UA | No |
| AS-Interface | No |
| Protocols (Ethernet) | |
| • TCP/IP | Yes |
| • DHCP | Yes |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| Number of connections | |
| • Number of connections, max. | 128; via integrated interfaces of the CPU and connected CPs / CMs |
| • Number of connections reserved for ES/HMI/web | 10 |
| • Number of connections via integrated interfaces | 88 |
| Redundancy mode | |
| Media redundancy | |
| — MRP | Yes; as MRP redundancy manager and/or MRP client |
| — MRPD | Yes |
| SIMATIC communication | |
| • S7 routing | No |
| • S7 communication, as server | Yes |
| • S7 communication, as client | Yes |
| Open IE communication | |
| • TCP/IP | Yes |
| — Data length, max. | 8 kbyte |
| — several passive connections per port, supported | Yes |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 8 kbyte |
| • UDP | Yes |
| — Data length, max. | 2 kbyte; 1 472 bytes for UDP broadcast |
| • DHCP | Yes |
| • DNS | Yes |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |
| • Encryption | Yes; Optional |
| Web server | |
| • supported | Yes |
| • HTTPS | Yes |

| | |
|--|--|
| <ul style="list-style-type: none"> • web API | Yes |
| <ul style="list-style-type: none"> — Number of sessions, max. | 30 |
| <ul style="list-style-type: none"> • User-defined websites | Yes |
| Further protocols | |
| <ul style="list-style-type: none"> • MODBUS | Yes |
| communication functions / header | |
| S7 communication | |
| <ul style="list-style-type: none"> • supported | Yes |
| <ul style="list-style-type: none"> • as server | Yes |
| <ul style="list-style-type: none"> • as client | Yes |
| <ul style="list-style-type: none"> • User data per job, max. | See online help (S7 communication, user data size) |
| Number of connections | |
| <ul style="list-style-type: none"> • overall | PG Connections: 4 reserved; HMI Connections: 4 reserved / 82 max; S7 Connections: 78 max; Open User Connections: 78 max; Web Connections: 2 reserved / 80 max; Total Connections: 10 reserved / 88 max |
| S7 message functions | |
| Number of login stations for message functions, max. | 32 |
| Program alarms | Yes |
| Number of configurable program messages, max. | 5 000 |
| Number of loadable program messages in RUN, max. | 2 500 |
| Number of simultaneously active program alarms | |
| <ul style="list-style-type: none"> • Number of program alarms | 600 |
| <ul style="list-style-type: none"> • Number of alarms for system diagnostics | 100 |
| <ul style="list-style-type: none"> • Number of alarms for motion technology objects | 160 |
| Test commissioning functions | |
| Status/control | |
| <ul style="list-style-type: none"> • Status/control variable | Yes |
| <ul style="list-style-type: none"> • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| <ul style="list-style-type: none"> • Forcing | Yes |
| Diagnostic buffer | |
| <ul style="list-style-type: none"> • present | Yes |
| Traces | |
| <ul style="list-style-type: none"> • Number of configurable Traces | 4 |
| <ul style="list-style-type: none"> • Memory size per trace, max. | 512 kbyte |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> • RUN/STOP LED | Yes |
| <ul style="list-style-type: none"> • ERROR LED | Yes |
| <ul style="list-style-type: none"> • MAINT LED | Yes |
| Supported technology objects | |
| Motion Control | |
| <ul style="list-style-type: none"> • Number of available Motion Control resources for technology objects | 800 |
| <ul style="list-style-type: none"> • Required Motion Control resources | |
| <ul style="list-style-type: none"> — per speed-controlled axis | 40 |
| <ul style="list-style-type: none"> — per positioning axis | 80 |
| <ul style="list-style-type: none"> — per synchronous axis | 160 |
| <ul style="list-style-type: none"> — per external encoder | 80 |
| <ul style="list-style-type: none"> — per output cam | 20 |
| <ul style="list-style-type: none"> — per cam track | 160 |
| <ul style="list-style-type: none"> — per probe | 40 |
| <ul style="list-style-type: none"> • Number of available Extended Motion Control resources for technology objects | 40 |
| <ul style="list-style-type: none"> • Required Extended Motion Control resources | |
| <ul style="list-style-type: none"> — per cam (1 000 points and 50 segments) | 2; 1000 points and 1 segment |
| <ul style="list-style-type: none"> — for each set of kinematics | 30 |
| <ul style="list-style-type: none"> • kinematics functions | |
| <ul style="list-style-type: none"> — kinematics with up to 4 interpolating axes | Yes |
| <ul style="list-style-type: none"> — kinematics with 5 or more interpolating axes | No |
| <ul style="list-style-type: none"> — user-defined kinematics | No |
| <ul style="list-style-type: none"> — SIMATIC Safe Kinematics | No |

- Positioning axis
 - Number of positioning axes at motion control cycle of 4 ms (typical value)
 - Number of positioning axes at motion control cycle of 8 ms (typical value)

10
10

Integrated Functions

| | |
|--|---|
| Counter | Yes |
| <ul style="list-style-type: none"> • Number of counters • Counting frequency, max. | 8 100 kHz; Ia.0 to Ia.5: 100 kHz (80 kHz in quadrature mode), Ia.6 to Ib.5: 30 kHz (20 kHz in quadrature mode) |
| Frequency measurement | Yes |
| PID controller | Yes |
| Number of pulse outputs | 8; individually assigned to CPU and Signal Board |
| Limit frequency (pulse) | 100 kHz |

Potential separation

| | |
|--|---|
| Potential separation digital inputs | |
| <ul style="list-style-type: none"> • Potential separation digital inputs • between the channels • Number of potential groups | Yes; field side to logic: 707 V DC (type test) No 1 |
| Potential separation digital outputs | |
| <ul style="list-style-type: none"> • Potential separation digital outputs • between the channels • Number of potential groups | Relays No 1 |

EMC

| | |
|---|--|
| Interference immunity against discharge of static electricity | |
| <ul style="list-style-type: none"> • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 — Test voltage at air discharge — Test voltage at contact discharge | Yes 8 kV 6 kV |
| Interference immunity to cable-borne interference | |
| <ul style="list-style-type: none"> • Interference immunity on supply lines acc. to IEC 61000-4-4 • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes Yes |
| Interference immunity against voltage surge | |
| <ul style="list-style-type: none"> • Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| <ul style="list-style-type: none"> • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |
| <ul style="list-style-type: none"> • Limit class A, for use in industrial areas • Limit class B, for use in residential areas | Yes; Group 1 Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011 |

Degree and class of protection

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Standards, approvals, certificates

| | |
|---------------------------|-----------------|
| Siemens Eco Profile (SEP) | Siemens EcoTech |
| CE mark | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | No |
| RCM (formerly C-TICK) | Yes |
| KC approval | No |
| Marine approval | No |

Ecological footprint

| | |
|---|-------------------------------|
| <ul style="list-style-type: none"> • environmental product declaration | Yes; type 2 acc. to ISO 14021 |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 68 kg |
| — global warming potential, (during production) [CO2 eq] | 14.4 kg |
| — global warming potential, (during operation) [CO2 eq] | 54.2 kg |
| — global warming potential, (after end of life cycle) | -0.723 kg |

[CO2 eq]

product functions / security / header

| | |
|------------------------|-----|
| signed firmware update | Yes |
| Secure Boot | Yes |
| safely removing data | No |

Ambient conditions

Free fall

- Fall height, max. 0.3 m; five times, in product package

Ambient temperature during operation

- min. -20 °C; No condensation
- max. 40 °C; 40 °C horizontal or 30 °C vertical at max. voltages and max. specifications
- horizontal installation, min. -20 °C; No condensation
- horizontal installation, max. 60 °C; at rated voltages, 50 % of max. specification and alternate IO active
- vertical installation, min. -20 °C; No condensation
- vertical installation, max. 50 °C; at rated voltages, 50 % of max. specification and alternate IO active

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Air pressure acc. to IEC 60068-2-13

- Operation, min. 540 hPa
- Operation, max. 1 140 hPa
- Storage/transport, min. 540 hPa
- Storage/transport, max. 1 140 hPa

Altitude during operation relating to sea level

- Installation altitude, min. -1 000 m
- Installation altitude, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Relative humidity

- Operation, max. 95 %; no condensation

Vibrations

- Vibration resistance during operation acc. to IEC 60068-2-6 3.5 mm from 5 - 8.4 Hz, 1g from 8.4 - 150 Hz
- Operation, tested according to IEC 60068-2-6 Yes

Shock testing

- tested according to IEC 60068-2-27 Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms

Pollutant concentrations

- SO2 at RH < 60% without condensation SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free

configuration / header

configuration / programming / header

| | |
|-----------------------------|-----|
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — SCL | Yes |

Know-how protection

- User program protection/password protection Yes

Access protection

- protection of confidential configuration data Yes
- Protection level: Write protection Yes
- Protection level: Read/write protection Yes
- Protection level: Complete protection Yes
- User administration Yes; device-wide
- Number of users 100
- Number of groups 100
- Number of roles 50

programming / cycle time monitoring / header

- adjustable Yes

Dimensions

| | |
|--------|--------|
| Width | 80 mm |
| Height | 125 mm |
| Depth | 100 mm |

Weights

Weight, approx. 417 g

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-24-22-07 |
| eClass | 12 | 27-24-22-07 |
| eClass | 9.1 | 27-24-22-07 |
| eClass | 9 | 27-24-22-07 |
| eClass | 8 | 27-24-22-07 |
| eClass | 7.1 | 27-24-22-07 |
| eClass | 6 | 27-24-22-07 |
| ETIM | 9 | EC000236 |
| ETIM | 8 | EC000236 |
| ETIM | 7 | EC000236 |
| IDEA | 4 | 3565 |
| UNSPSC | 15 | 32-15-17-05 |

Approvals / Certificates

General Product Approval



[KC](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



EMV

For use in hazardous locations

Test Certificates

[KC](#)



[CCC-Ex](#)

[Type Test Certificates/Test Report](#)

Environment

Industrial Communication



Siemens EcoTech



[PROFINET](#)

last modified:

4/1/2025

ماکان کنترول