



SIMATIC DP, CPU 1513pro-2 PN for ET 200pro, central processing unit with 300 KB work memory for program and 1.5 MB for data, 1st interface: PROFINET IRT with 3-port switch, 2nd interface: PROFINET RT, 40 ns bit performance, Degree of protection: IP65/67, SIMATIC Memory Card required connection module required

General information	
Product type designation	CPU 1513pro-2 PN
HW functional status	FS01
Firmware version	V2.8
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes; Via X1, with minimum OB 6x cycle of 500 µs
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V16
Configuration control	
via dataset	No
Control elements	
Mode selector switch	1
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption (rated value)	0.31 A
Current consumption, max.	0.4 A
Inrush current, max.	0.4 A; Rated value
I <sup>2</sup> t	0.001 A <sup>2</sup> ·s
from supply voltage 1L+, max.	0.4 A
Power	
Infeed power to the backplane bus	2.275 W
Power loss	
Power loss, typ.	5.3 W
Memory	
Number of slots for SIMATIC memory card	1
SIMATIC memory card required	Yes
Work memory	
• integrated (for program)	300 kbyte
• integrated (for data)	1.5 Mbyte
Load memory	
• Plug-in (SIMATIC Memory Card), max.	32 Gbyte
Backup	
• maintenance-free	Yes
CPU processing times	

for bit operations, typ.	40 ns
for word operations, typ.	48 ns
for fixed point arithmetic, typ.	64 ns
for floating point arithmetic, typ.	256 ns
<b>CPU-blocks</b>	
Number of elements (total)	2 000; Blocks (OB, FB, FC, DB) and UDTs
<b>DB</b>	
• Number range	1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999
• Size, max.	1.5 Mbyte; For DBs with absolute addressing, the max. size is 64 KB
<b>FB</b>	
• Number range	0 ... 65 535
• Size, max.	300 kbyte
<b>FC</b>	
• Number range	0 ... 65 535
• Size, max.	300 kbyte
<b>OB</b>	
• Size, max.	300 kbyte
• Number of free cycle OBs	100
• Number of time alarm OBs	20
• Number of delay alarm OBs	20
• Number of cyclic interrupt OBs	20; With minimum OB 3x cycle of 500 µs
• Number of process alarm OBs	50
• Number of DPV1 alarm OBs	3
• Number of isochronous mode OBs	1
• Number of technology synchronous alarm OBs	2
• Number of startup OBs	100
• Number of asynchronous error OBs	4
• Number of synchronous error OBs	2
• Number of diagnostic alarm OBs	1
<b>Nesting depth</b>	
• per priority class	24
<b>Counters, timers and their retentivity</b>	
<b>S7 counter</b>	
• Number	2 048
Retentivity	
— adjustable	Yes
<b>IEC counter</b>	
• Number	Any (only limited by the main memory)
Retentivity	
— adjustable	Yes
<b>S7 times</b>	
• Number	2 048
Retentivity	
— adjustable	Yes
<b>IEC timer</b>	
• Number	Any (only limited by the main memory)
Retentivity	
— adjustable	Yes
<b>Data areas and their retentivity</b>	
Retentive data area (incl. timers, counters, flags), max.	128 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 88 KB
<b>Flag</b>	
• Size, max.	16 kbyte
• Number of clock memories	8; 8 clock memory bit, grouped into one clock memory byte
<b>Data blocks</b>	
• Retentivity adjustable	Yes
• Retentivity preset	No
<b>Local data</b>	
• per priority class, max.	64 kbyte; max. 16 KB per block
<b>Address area</b>	

Number of IO modules	2 048; max. number of modules / submodules
<b>I/O address area</b>	
• Inputs	32 kbyte; All inputs are in the process image
• Outputs	32 kbyte; All outputs are in the process image
<b>per integrated IO subsystem</b>	
— Inputs (volume)	8 kbyte
— Outputs (volume)	8 kbyte
<b>Hardware configuration</b>	
Number of distributed IO systems	32; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link)
<b>Number of IO Controllers</b>	
• integrated	2
• Via CM	0
<b>Rack</b>	
• Modules per rack, max.	16; Expansion width max. 1.2 m
• Number of lines, max.	1
<b>Time of day</b>	
<b>Clock</b>	
• Type	Hardware clock
• Backup time	6 wk; At 40 °C ambient temperature, typically
• Deviation per day, max.	10 s; Typ.: 2 s
<b>Operating hours counter</b>	
• Number	16
<b>Clock synchronization</b>	
• supported	Yes
• in AS, master	Yes
• in AS, device	Yes
• on Ethernet via NTP	Yes
<b>Interfaces</b>	
Number of PROFINET interfaces	2
Number of PROFIBUS interfaces	0
<b>1. Interface</b>	
<b>Interface types</b>	
• RJ 45 (Ethernet)	Yes; X1 P3
• Number of ports	3; 2x M12 + 1x RJ45
• integrated switch	Yes
<b>Protocols</b>	
• IP protocol	Yes; IPv4
• PROFINET IO Controller	Yes
• PROFINET IO Device	Yes
• SIMATIC communication	Yes
• Open IE communication	Yes; Optionally also encrypted
• Web server	Yes
• Media redundancy	Yes; MRP Automanager according to IEC 62439-2 Edition 2.0
<b>PROFINET IO Controller</b>	
<b>Services</b>	
— PG/OP communication	Yes
— Isochronous mode	Yes
— Direct data exchange	Yes; Requirement: IRT and isochronous mode (MRPD optional)
— IRT	Yes
— PROFlenergy	Yes
— Prioritized startup	Yes; Max. 32 PROFINET devices
— Number of connectable IO Devices, max.	128; In total, up to 512 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET
— Of which IO devices with IRT, max.	64
— Number of connectable IO Devices for RT, max.	128
— of which in line, max.	128
— Number of IO Devices that can be simultaneously activated/deactivated, max.	8; in total across all interfaces
— Number of IO Devices per tool, max.	8
— Updating times	The minimum value of the update time also depends on communication share

set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data

**Update time for IRT**

- for send cycle of 250  $\mu$ s 250  $\mu$ s to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 500  $\mu$ s of the isochronous OB is decisive
- for send cycle of 500  $\mu$ s 500  $\mu$ s to 8 ms
- for send cycle of 1 ms 1 ms to 16 ms
- for send cycle of 2 ms 2 ms to 32 ms
- for send cycle of 4 ms 4 ms to 64 ms
- With IRT and parameterization of "odd" send cycles Update time = set "odd" send clock (any multiple of 125  $\mu$ s: 375  $\mu$ s, 625  $\mu$ s ... 3 875  $\mu$ s)

**Update time for RT**

- for send cycle of 250  $\mu$ s 250  $\mu$ s to 128 ms
- for send cycle of 500  $\mu$ s 500  $\mu$ s to 256 ms
- for send cycle of 1 ms 1 ms to 512 ms
- for send cycle of 2 ms 2 ms to 512 ms
- for send cycle of 4 ms 4 ms to 512 ms

**PROFINET IO Device**

**Services**

- PG/OP communication Yes
- Isochronous mode No
- IRT Yes
- PROFinergy Yes; per user program
- Prioritized startup No
- Shared device Yes
- Number of IO Controllers with shared device, max. 4
- Asset management record Yes; per user program

**2. Interface**

**Interface types**

- RJ 45 (Ethernet) No
- Number of ports 1; 1x M12
- integrated switch No

**Protocols**

- IP protocol Yes; IPv4
- PROFINET IO Controller Yes
- PROFINET IO Device Yes
- SIMATIC communication Yes
- Open IE communication Yes; Optionally also encrypted
- Web server Yes
- Media redundancy No

**PROFINET IO Controller**

**Services**

- PG/OP communication Yes
- Isochronous mode No
- Direct data exchange No
- IRT No
- PROFinergy Yes
- Prioritized startup No
- Number of connectable IO Devices, max. 32; In total, up to 512 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET
- Number of connectable IO Devices for RT, max. 32
- of which in line, max. 32
- Number of IO Devices that can be simultaneously activated/deactivated, max. 8; in total across all interfaces
- Number of IO Devices per tool, max. 8
- Updating times The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data

**Update time for RT**

- for send cycle of 1 ms 1 ms to 512 ms

**PROFINET IO Device**

**Services**

- PG/OP communication Yes

— Isochronous mode	No
— IRT	No
— PROFlenergy	Yes; per user program
— Prioritized startup	No
— Shared device	Yes
— Number of IO Controllers with shared device, max.	4
— Asset management record	Yes; per user program

### Interface types

<b>RJ 45 (Ethernet)</b>	
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
• Industrial Ethernet status LED	Yes

### Protocols

PROFlsafe	No
-----------	----

### Number of connections

• Number of connections, max.	128; Via integrated interfaces of the CPU
• Number of connections reserved for ES/HMI/web	10
• Number of connections via integrated interfaces	128
• Number of S7 routing paths	16

### Redundancy mode

• H-Sync forwarding	Yes
---------------------	-----

### Media redundancy

— MRP	Yes; as MRP redundancy manager and/or MRP client
— MRPD	Yes; Requirement: IRT
— Switchover time on line break, typ.	200 ms; For MRP, bumpless for MRPD
— Number of stations in the ring, max.	50

### SIMATIC communication

• S7 routing	Yes
• S7 communication, as server	Yes
• S7 communication, as client	Yes
• User data per job, max.	See online help (S7 communication, user data size)

### Open IE communication

• TCP/IP	Yes
— Data length, max.	64 kbyte
— several passive connections per port, supported	Yes
• ISO-on-TCP (RFC1006)	Yes
— Data length, max.	64 kbyte
• UDP	Yes
— Data length, max.	2 kbyte; 1 472 bytes for UDP broadcast
— UDP multicast	Yes; Max. 5 multicast circuits
• DHCP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes

### Web server

• HTTP	Yes; Standard and user pages
• HTTPS	Yes; Standard and user pages

### OPC UA

• Runtime license required	Yes; "Small" license required
• OPC UA Client	Yes; Data access (read, write), method call, custom address space
— Application authentication	Yes
— Security policies	Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256
— User authentication	"anonymous" or by user name & password
— Number of connections, max.	4
— Number of nodes of the client interfaces, recommended max.	1 000
— Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/OPC-UA_WriteList	300
— Number of elements for one call of OPC-UA_WriteList	20

OPC-UA\_NameSpaceGetIndexList, max.  
 — Number of elements for one call of  
 OPC-UA\_MethodGetHandleList, max.  
 — Number of simultaneous calls of the client  
 instructions for session management, per connection,  
 max.  
 — Number of simultaneous calls of the client  
 instructions for data access, per connection, max.  
 — Number of registerable nodes, max.  
 — Number of registerable method calls of  
 OPC-UA\_MethodCall, max.  
 — Number of inputs/outputs when calling  
 OPC-UA\_MethodCall, max.

100  
 1  
 5  
 5 000  
 100  
 20

• OPC UA Server

— Application authentication  
 — Security policies  
 — User authentication  
 — Number of sessions, max.  
 — Number of accessible variables, max.  
 — Number of registerable nodes, max.  
 — Number of subscriptions per session, max.  
 — Sampling interval, min.  
 — Publishing interval, min.  
 — Number of server methods, max.  
 — Number of inputs/outputs per server method, max.  
 — Number of monitored items, recommended max.  
 — Number of server interfaces, max.  
 — Number of nodes for user-defined server interfaces,  
 max.

Yes; Data access (read, write, subscribe), method call, custom address space;  
 embedded 2017 UA server profile V1.02

Yes

Available security policies: None, Basic128Rsa15, Basic256Rsa15,  
 Basic256Sha256

"anonymous" or by user name & password

32  
 50 000  
 10 000  
 20  
 100 ms  
 500 ms  
 20  
 20  
 1 000; for 1 s sampling interval and 1 s send interval  
 10  
 1 000

Further protocols

• MODBUS

Yes; MODBUS TCP

S7 message functions

Number of login stations for message functions, max.

32

Program alarms

Yes

Number of configurable program messages, max.

5 000; Program messages are generated by the "Program\_Alarm" block,  
 ProDiag or GRAPH

Number of loadable program messages in RUN, max.

2 500

Number of simultaneously active program alarms

- Number of program alarms
- Number of alarms for system diagnostics
- Number of alarms for motion technology objects

600  
 100  
 80

Test commissioning functions

Joint commission (Team Engineering)

Yes; Parallel online access possible for up to 5 engineering systems

Status block

Yes; Up to 8 simultaneously (in total across all ES clients)

Single step

No

Number of breakpoints

8

Status/control

- Status/control variable
- Variables
- Number of variables, max.
  - of which status variables, max.
  - of which control variables, max.

Yes  
 Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters  
 200; per job  
 200; per job

Forcing

- Forcing
- Forcing, variables
- Number of variables, max.

Yes  
 Peripheral inputs/outputs  
 200

Diagnostic buffer

- present
- Number of entries, max.
  - of which powerfail-proof

Yes  
 1 000  
 500

Traces

- Number of configurable Traces

4; Up to 512 KB of data per trace are possible

**Interrupts/diagnostics/status information****Diagnostics indication LED**

• RUN/STOP LED	Yes
• ERROR LED	Yes
• MAINT LED	Yes
• Monitoring of the supply voltage (PWR-LED)	Yes; green "24 V DC" LED
• Connection display LINK TX/RX	Yes

**Supported technology objects**

**Motion Control** Yes; Note: The number of axes affects the cycle time of the PLC program; selection guide via the TIA Selection Tool or SIZER

• Number of available Motion Control resources for technology objects	800
• Required Motion Control resources	
— per speed-controlled axis	40
— per positioning axis	80
— per synchronous axis	160
— per external encoder	80
— per output cam	20
— per cam track	160
— per probe	40
• Positioning axis	
— Number of positioning axes at motion control cycle of 4 ms (typical value)	5
— Number of positioning axes at motion control cycle of 8 ms (typical value)	10

**Controller**

• PID_Compact	Yes; Universal PID controller with integrated optimization
• PID_3Step	Yes; PID controller with integrated optimization for valves
• PID-Temp	Yes; PID controller with integrated optimization for temperature

**Counting and measuring**

• High-speed counter	Yes
----------------------	-----

**Ambient conditions****Ambient temperature during operation**

• horizontal installation, min.	-25 °C
• horizontal installation, max.	55 °C
• vertical installation, min.	-25 °C
• vertical installation, max.	55 °C

**Ambient temperature during storage/transportation**

• min.	-40 °C
• max.	70 °C

**Altitude during operation relating to sea level**

• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
---	--

**configuration / header****configuration / programming / header****Programming language**

— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes

**Know-how protection**

• User program protection/password protection	Yes
• Copy protection	Yes
• Block protection	Yes

**Access protection**

• Protection level: Write protection	Yes
• Protection level: Read/write protection	Yes
• Protection level: Complete protection	Yes

**programming / cycle time monitoring / header**

• lower limit	adjustable minimum cycle time
• upper limit	adjustable maximum cycle time

**Dimensions**

Width	135 mm
Height	130 mm
Depth	65 mm
<b>Weights</b>	
Weight, approx.	614 g
<b>Classifications</b>	

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603
IDEA	4	3565
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

**General Product Approval**

[Miscellaneous](#)



[Miscellaneous](#)



**General Product Approval** | **Maritime application**

[KC](#)



[NK / Nippon Kaiji Kyokai](#)

**Maritime application** | **other** | **Industrial Communication**



[CCS \(China Classification Society\)](#)



[PROFINET](#)

[PROFINET](#)

last modified:

12/8/2024