



SIMATIC DP, electronic module ET 200SP, F-AI 4xI0(4)..20 mA HF fail-safe analog inputs up to PL e (ISO 13849) up to SIL 3 (IEC 61508)

General information	
Product type designation	F-AI 4xI 0(4)..20mA 2-/4-wire HF
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V15 with HSP 203
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption (rated value)	0.38 A
Current consumption, max.	0.4 A
Encoder supply	
24 V encoder supply	
• 24 V	Yes; min. L+ (-1.5 V)
• Short-circuit protection	Yes
• Output current, max.	300 mA; total current of all encoders/channels
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
• Inputs	14 byte; S7-300/400F CPU, 13 byte
• Outputs	5 byte; S7-300/400F CPU, 4 byte
Hardware configuration	
Automatic encoding	Yes
• Electronic coding element type F	Yes
Analog inputs	
Number of analog inputs	4

<ul style="list-style-type: none"> • For current measurement 	4
permissible input current for current input (destruction limit), max.	35 mA
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) • 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) 	Yes 125 Ω Yes 125 Ω
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Integration time (ms) • Interference voltage suppression for interference frequency f_1 in Hz 	16 bit Yes 20 / 16,667 50 / 60 Hz
Smoothing of measured values	
<ul style="list-style-type: none"> • Number of smoothing levels • parameterizable • Step: None • Step: low • Step: Medium • Step: High 	7 Yes Yes; 1x conversion cycle time Yes; 2x / 4x conversion cycle time Yes; 8x / 16x conversion cycle time Yes; 32x / 64x conversion cycle time
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for current measurement as 2-wire transducer <ul style="list-style-type: none"> — Burden of 2-wire transmitter, max. • for current measurement as 4-wire transducer 	Yes 650 Ω Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.023 %/K
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	2 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	0.1 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. • Common mode interference, min. 	40 dB 70 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm • Limit value alarm 	Yes No
Diagnoses	
<ul style="list-style-type: none"> • Monitoring the supply voltage • Wire-break • Short-circuit 	Yes Yes Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> • RUN LED • ERROR LED • Monitoring of the supply voltage (PWR-LED) • Channel status display • for channel diagnostics • for module diagnostics 	Yes; green LED Yes; red LED Yes; green PWR LED Yes; green LED Yes; red LED Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> • between the channels 	No

<ul style="list-style-type: none"> • between the channels and backplane bus • between the channels and the power supply of the electronics 	Yes		
Permissible potential difference			
between the inputs (UCM)	10 Vpp		
Isolation			
Isolation tested with	707 V DC (type test)		
Standards, approvals, certificates			
Ecological footprint			
<ul style="list-style-type: none"> • environmental product declaration 	Yes		
Global warming potential			
— global warming potential, (total) [CO2 eq]	88.3 kg		
— global warming potential, (during production) [CO2 eq]	13.1 kg		
— global warming potential, (during operation) [CO2 eq]	76.6 kg		
— global warming potential, (after end of life cycle) [CO2 eq]	-1.37 kg		
Highest safety class achievable in safety mode			
<ul style="list-style-type: none"> • Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 61508 	PLe	Cat. 4	SIL 3
Probability of failure (for service life of 20 years and repair time of 100 hours)			
— Low demand mode: PFDavg in accordance with SIL3	< 5.00E-05		
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h		
Ambient conditions			
Ambient temperature during operation			
<ul style="list-style-type: none"> • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	0 °C	60 °C	0 °C
		50 °C	
Dimensions			
Width	15 mm		
Height	73 mm		
Depth	58 mm		
Weights			
Weight, approx.	48 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-01
	eClass	12	27-24-26-01
	eClass	9.1	27-24-26-01
	eClass	9	27-24-26-01
	eClass	8	27-24-26-01
	eClass	7.1	27-24-26-01
	eClass	6	27-24-26-01
	ETIM	9	EC001596
	ETIM	8	EC001596
	ETIM	7	EC001596
	IDEA	4	3562
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			

Miscellaneous



Manufacturer Declaration



For use in hazardous locations



CCC-Ex

FM



Miscellaneous

Functional Safety

Maritime application



Type Examination Certificate



Maritime application

other

NK / Nippon Kaiji Kyokai



CCS (China Classification Society)



PROFIsafe

last modified:

10/9/2024



ماکان کنترول