

SIMATIC ET 200SP, BusAdapter BA 2xSCRJ, 2 SCRJ FO connections



General information		
Product type designation	BA 2xSCRJ	
HW functional status	from FS04	
Interfaces		
Number of PROFINET interfaces	1; 2 ports (switch) SCRJ FO	
Supports protocol for PROFINET IO		
• Number of SCRJ ports	2	
Cable length		
— PCF	100 m	
— Plastic FOC (POF)	50 m	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-25 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-25 °C	
• vertical installation, max.	50 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual	
Dimensions		
Width	20 mm	
Height	69.5 mm	
Depth	59 mm	
Weights		
Weight, approx.	50 g	
Classifications		
	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)



[KC](#)



For use in hazardous locations



[FM](#)

[CCC-Ex](#)



[Miscellaneous](#)

Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

Environment



[CCS \(China Classification Society\)](#)



last modified:

4/7/2025

ماکان کنترول