



SIMATIC ET 200SP, BusAdapter BA SCRJ/RJ45, media converter FOC-CU 1x SCRJ FO connection and, 1x RJ45 connection

General information		
Product type designation	BA SCRJ/RJ45	
HW functional status	from FS04	
Interfaces		
Number of PROFINET interfaces	1; 2 ports (switch) SCRJ/RJ45	
Supports protocol for PROFINET IO		
• Number of RJ45 ports	1	
• Number of SCRJ ports	1	
Cable length		
— PCF	100 m	
— Plastic FOC (POF)	50 m	
— Cu conductors	100 m	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-25 °C	
• horizontal installation, max.	60 °C	
• vertical installation, min.	-25 °C	
• vertical installation, max.	50 °C	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual	
Dimensions		
Width	20 mm	
Height	69.5 mm	
Depth	59 mm	
Weights		
Weight, approx.	50 g	
Classifications		
	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584

ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval	Maritime application	other
--------------------------	----------------------	-------



[Miscellaneous](#)



[CCS \(China Classification Society\)](#)



other	Railway	Environment
-------	---------	-------------

[Confirmation](#)

[Confirmation](#)



[Environmental Confirmations](#)

[Environmental Confirmations](#)

last modified:

4/7/2025

ماکان کنترول