

SIMATIC ET 200SP, server module for BaseCarrier pack quantity: 1 unit,



General information	
Product type designation	server modules for BaseCarrier
HW functional status	from FS01
Input current	
Current consumption, max.	30 mA
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> • min. • horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max. 	No condensation -30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> • Installation altitude above sea level, max. 	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	25 g
Classifications	

	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates	
General Product Approval	For use in hazardous locations

[Manufacturer Declaration](#)



For use in hazardous locations

[CCC-Ex](#)

[FM](#)



[Type Examination Certificate](#)

[Miscellaneous](#)



last modified:

7/2/2025

ماکان کنترول