



PRODUCT-DETAILS

ACS580-04-585A-4

LV AC general purpose drive module, IEC: Pn 315 kW, 585 A (ACS580-04-585A-4)



General Information	
Global Commercial Alias	ACS580-04-585A-4
Product ID	3ABD00036862-D
ABB Type Designation	ACS580-04-585A-4
Catalog Description	LV AC general purpose drive module, IEC: Pn 315 kW, 585 A (ACS580-04-585A-4)
Long Description	<p>The ACS580-04 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans, and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture. All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. A versatile and straightforward settings menu and assistants enable fast setup, commissioning, use, and maintenance, while a rugged and robust design makes it a good fit for various environments. With the ACS580 drives, you can easily take full control of your processes to comprehensively manage your plant. The ACS580-04 drive module comes in an IP00 enclosure as standard for cabinet installation. In addition, an IP20 enclosure is available.</p>

Ordering	
Customs Tariff Number	85044099
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters

Invoice Description	ACS580-04-585A-4 PN:315kW, IN: 585A
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	161 kg
Product Net Depth / Length	529 mm
Product Net Height	1462 mm
Product Net Width	345 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Height	500 mm
Package Level 1 Width	400 mm
Package Level 1 Units	0 carton

Technical

Number of Phases	3-phases
Degree of Protection	IP00
Enclosure Type NEMA	Open Type
Frequency (f)	47.5 ... 63 Hz
Frame Size	R10
Input Voltage (U_{in})	380 ... 500 V
Mounting Type	Module_NO UNIT\$
Output Current, Normal Use (I_n)	585 A
Output Current, Light-Overload Use (I_{LD})	575 A
Output Current, Heavy-Duty Use (I_{HD})	429 A
Output Power, Normal Use (P_n)	315 kW
Output Power, Light-Overload Use (P_{LD})	315 kW
Output Power, Heavy-Duty Use (P_{HD})	250 kW
Efficiency Level	IE2
Complete Drive Module Efficiency (IEC61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	1889 W	0.4 %	93.2 %
0 / 50 %	2690 W	0.6 %	95.0 %
0 / 100 %	4866 W	1.0 %	95.4 %
50 / 25 %	2030 W	0.4 %	96.4 %
50 / 50 %	2990 W	0.6 %	97.3 %
50 / 100 %	5617 W	1.2 %	97.4 %
90 / 50 %	3427 W	0.7 %	98.2 %
90 / 100 %	6840 W	1.4 %	98.2 %

Environmental

WEEE Category 4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

UNSPSC 39122001

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-04 - Drive module



ماکان کنترول